
## **KERRIA PLUS** Shower doors

Product code: KTSUN43P EAN: 5907650819974 Color: nero Warranty [years]: 2







Model	Size [mm]	A [mm]	B [mm]	C [mm]	A+XKC00PX02	A+KTS_X22X
KTSUX42P + KTS_X00X	800x2000	775-800	255-280	520	820-860	800-830
KTSUX41P + KTS_X00X	900x2000	875-900	355-380	520	920-960	900-930
KTSUX43P + KTS_X00X	1000x2000	975-1000	405-430	570	1020-1060	1000-1030
KTSUX44P + KTS_X00X	1100x2000	1075-1100	455-480	620	1120-1160	1100-1130
KTSUX45P + KTS_X00X	1200x2000	1175-1200	505-530	670	1220-1260	1200-1230

## Shower door

Width [mm]	1000
Height [mm]	2000
Glass thickness [mm]	6
Glass finish	transparent
installation	to be completed with I/TC
ווואנמנומנוטוו	to be completed with KTS
Instattation	walk-in, to be completed
Instattation	•

🐝 deante

## Features:

- Important! For recessed installation, be sure to buy the appropriate KTS\_NOOX or KTS\_000X profile
- Active Cover coating
- TOTALWHITE transparent glass
- Profiles leveling the curvature of the walls
- Covering of assembly elements
- Possibility to install the cabin without a shower tray, directly on the tiles
- Dedicated cleaning agent, safe for cleaned surfaces
- Dedicated to Active Cover surfaces
- Reversible door that allows the cabin to be mounted on the right or left side
- The profile system makes it possible to reduce the curvature of the walls
- Hydrophobic Active-Cover coating that makes it easier for water to run off the glass
- Safe and durable tempered glass
- Only the best materials, the quality of which has been confirmed by laboratory tests
- Precise door closing through lifting hinges
- The railings give the structure rigidity
- Resistance to impacts, chemicals and stains in accordance with PN-EN 14428+A1:2008 norm, confirmed by tests of the Institute of Ceramics and Building Materials